



RECOMMEND PCB LAYOUT  
(TOLERANCE=±0.05)

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 05/09/05'		

- NOTES:
- SPECIFICATIONS:
    - CONTACT RESISTANCE: 30mΩ max.
    - INSULATOR RESISTANCE: 1000MΩ min.AT DC 500V.
    - CURRENT RATING: 1.5A.
    - VOLTAGE RATING: 30V AC/DC.
    - DIELECTRIC STRENGTH: AC 500V FOR 1 Minute.
  - MATERIALS:
    - HOUSING: PBT+30% GLASS FIBER(UL 94-0).
    - CONTACT: COPPER ALLOY
    - SHELL: COPPER ALLOY.
  - PRODUCT NUMBER CODE:

DS1095-X X X X

- CONTACT PLATING
  - 0: Selective gold flash
  - 03: Selective gold 3u"
  - 30: Selective gold 30u"
- MOUNTING TYPE
  - R: R/A
- SHELL PLATING:
  - N: Nickel
  - 6: Tin
- COLOR OF HOUSING:
  - W: WHITE
  - B: Black
- SERIES No. DS1095

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE	
X.	±0.60	X.	±5'		USB A TYPE Single port Female TYPE	
.X	±0.38	.X	±3'	mm		
.XX	±0.25	.XX	±2'		SHEET SIZE A4	
DRAWING TYPE				CUSTOMER	SERIES	DS1095 SERIES
SCALE				1:1	USBA-1J 1095	
DRAWING NO.				C-DS1095-XXXX	SHEET 1 OF 1	